

US Army Corps of Engineers
Philadelphia District

STA. 0+000 to STA. 14+000 -- 17 & 18 JAN 24
STA. 14+000 to STA. 24+000 -- 02 JAN 24
STA. 24+000 to STA. 29+700 -- 28 DEC 23

U.S. ARMY CORPS OF ENGINEERS
PHILADELPHIA DISTRICT

Surveyed By:
Plotted By: E. Anthony
Checked By:
Drawing No:
Plot Scale:
Approved: Chief, Survey Section

Chesapeake and Delaware Canal
Delaware River to St. Georges Bridges
Examination
STA. -0+400 TO STA. 26+000

E-CD-113

VICINITY MAP



1. THIS SURVEY MEETS STANDARDS AS OUTLINED IN CORPS OF ENGINEERS' HYDROGRAPHIC SURVEY MANUAL EM1110-2-1003, DATED NOVEMBER 30, 2013 FOR NAVIGATION AND DREDGING SUPPORT SURVEYS.

2. HORIZONTAL REFERENCE - NAD 83, DELAWARE STATE PLANE, ZONE 0700, U.S. FOOT.

3. VERTICAL REFERENCE – MEAN LOWER LOW WATER, WHICH IS BELOW N.A.V.D. 88 BY THE FOLLOWING:
2. 62' from STA. 26+000 to STA. 25+516.80
2.64' from STA. 25+516.80 to STA. 24+586.34
2.66' from STA. 24+586.34 to STA. 23+655.72
2.68' from STA. 23+655.72 to STA. 22+448.76
2.70' from STA. 22+448.76 to STA. 21+672.19
2.72' from STA. 21+672.19 to STA. 20+895.63
2.73' from STA. 20+895.63 to STA. 20+119.06
2.75' from STA. 20+119.06 to STA. 19+342.49
2.95' from STA. 19+342.49 to STA. -0+400

4. GEOID 12B AND NOAA TIDAL EPOCH: 1983 – 2001 WERE USED. SOUNDINGS ARE EXPRESSED IN FEET AND TENTHS AND REFER TO MEAN LOWER LOW WATER.

5. SOUNDINGS WERE SELECTED FOR PLOTTING PURPOSES ONLY, USING THE MINIMUM DEPTH WITHIN A 30'X30' CELL SHIFTED TO THE CELL CENTER.

6. CONTOURS DEPICT ACTUAL LOCATION OF BATHYMETRY AND DO NOT NECESSARILY REFLECT PLOTTED SOUNDING LOCATIONS.

7. CONTOURS WERE GENERATED USING THE MINIMUM DEPTH WITHIN A 15'X15' CELL.

8. HYPACK, INC. SOFTWARE WAS USED TO PERFORM THE SOUNDING SELECTION AND CONTOUR GENERATION.

9. THE INFORMATION DEPICTED ON THIS MAP REPRESENT THE RESULTS OF SURVEYS MADE ON THE DATES INDICATED AND CAN ONLY BE CONSIDERED AS INDICATING THE GENERAL CONDITIONS EXISTING AT THAT TIME.

10. THE POSITIONS OF THE AIDS TO NAVIGATION ARE PROVIDED FOR INFORMATION ONLY, AND SHOULD NOT BE USED FOR NAVIGATION.

11. THE LIMITS OF THE FEDERAL CHANNEL DEPICT THE MOST CURRENT CHANNEL FRAMEWORK AVAILABLE WHICH CAN ALSO BE DOWNLOADED HERE:

http://navigation.usace.army.mil/Survey/Framework

12. BASE MAPPING LINEWORK OR ORTHOPHOTOGRAPHY HAS BEEN COMPILED FROM A VARIETY OF SOURCES AND DATES AND IS INTENDED TO PORTRAY GENERAL CHARACTERISTICS OF THE SHORELINE AND OTHER FEATURES. TEMPORAL CHANGES MAY HAVE OCCURRED SINCE THIS DATA SET WAS COLLECTED AND SOME PARTS OF THE DATA MAY NO LONGER BE AN ACCURATE REPRESENTATION OF THE SURFACE CONDITIONS.

Scale in Feet
200 0 200 400 600

- Shoalest Sounding
- CenterLine
- ToeLine
- QuarterLine
- StationLine
- 35 - 48.39
- 34 - 35
- 33 - 34
- 32 - 33
- 31 - 32
- 30 - 31
- 19.69 - 30



US Army Corps of Engineers
Philadelphia District

STA. 0+000 to STA. 14+000 -- 17 & 18 JAN 24
STA. 14+000 to STA. 24+000 -- 02 JAN 24
STA. 24+000 to STA. 29+700 -- 28 DEC 23

DISCLAIMER
The materials are provided for general information only. It is not intended for use as a navigation aid. NOAA ENC® charts are the official source for navigation. GIS readers by mariners. Any navigational use of this product is at the user's own risk. The government makes no warranty as to the accuracy, reliability, or completeness of this data. At best, hydrographic survey are performed at discrete points and intervals. Conditions within the datasets of the survey equipment, computers, and plant them. Wind, waves, currents, and other marine waters of the United States. Survey equipment and operators are also subject to human error.

The materials are provided "as is." The government makes no warranty, expressed or implied, as to accuracy about the quality/or suitability of the materials, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. The government makes no warranty as to the truth, accuracy or completeness of any data, information or representations as to the truth, accuracy or completeness of any data, information or representations as to the truth, accuracy or completeness of any data, information or representations. The government disclaims any liability for the use of this data by others and the government built not be liable for any damages incurred directly or indirectly from use or reliance on the contents of this document.

U.S. ARMY CORPS OF ENGINEERS PHILADELPHIA DISTRICT	Surveyed By:
	Plotted By: E. Anthony
Drawing No:	Checked By:
Plot Scale:	Approved: Chief, Survey Section

Chesapeake and Delaware Canal
Delaware River to St. Georges Bridges
Examination
STA. -0+400 TO STA. 26+000

E-CD-113

VICINITY MAP

1. THIS SURVEY MEETS STANDARDS AS OUTLINED IN CORPS OF ENGINEERS' HYDROGRAPHIC SURVEY MANUAL EM1110-2-1003, DATED NOVEMBER 30, 2013 FOR NAVIGATION AND DREDGING SUPPORT SURVEYS.

2. HORIZONTAL REFERENCE - NAD 83, DELAWARE STATE PLANE, ZONE 0700, U.S. FOOT.

3. VERTICAL REFERENCE – MEAN LOWER LOW WATER, WHICH IS BELOW N.A.V.D. 88 BY THE FOLLOWING:
2. 62' from STA. 26+000 to STA. 25+516.80
2.64' from STA. 25+516.80 to STA. 24+586.34
2.66' from STA. 24+586.34 to STA. 23+655.72
2.68' from STA. 23+655.72 to STA. 22+448.76
2.70' from STA. 22+448.76 to STA. 21+672.19
2.72' from STA. 21+672.19 to STA. 20+895.63
2.73' from STA. 20+895.63 to STA. 20+119.06
2.75' from STA. 20+119.06 to STA. 19+342.49
2.95' from STA. 19+342.49 to STA. -0+400

4. GEOID 12B AND NOAA TIDAL EPOCH: 1983 – 2001 WERE USED. SOUNDINGS ARE EXPRESSED IN FEET AND TENTHS AND REFER TO MEAN LOWER LOW WATER.

5. SOUNDINGS WERE SELECTED FOR PLOTTING PURPOSES ONLY, USING THE MINIMUM DEPTH WITHIN A 30'X30' CELL SHIFTED TO THE CELL CENTER.

6. CONTOURS DEPICT ACTUAL LOCATION OF BATHYMETRY AND DO NOT NECESSARILY REFLECT PLOTTED SOUNDING LOCATIONS.

7. CONTOURS WERE GENERATED USING THE MINIMUM DEPTH WITHIN A 15'X15' CELL.

8. HYPACK, INC. SOFTWARE WAS USED TO PERFORM THE SOUNDING SELECTION AND CONTOUR GENERATION.

9. THE INFORMATION DEPICTED ON THIS MAP REPRESENT THE RESULTS OF SURVEYS MADE ON THE DATES INDICATED AND CAN ONLY BE CONSIDERED AS INDICATING THE GENERAL CONDITIONS EXISTING AT THAT TIME.

10. THE POSITIONS OF THE AIDS TO NAVIGATION ARE PROVIDED FOR INFORMATION ONLY, AND SHOULD NOT BE USED FOR NAVIGATION.

11. THE LIMITS OF THE FEDERAL CHANNEL DEPICT THE MOST CURRENT CHANNEL FRAMEWORK AVAILABLE WHICH CAN ALSO BE DOWNLOADED HERE:

http://navigation.usace.army.mil/Survey/Framework

12. BASE MAPPING LINEWORK OR ORTHOPHOTOGRAPHY HAS BEEN COMPILED FROM A VARIETY OF SOURCES AND DATES AND IS INTENDED TO PORTRAY GENERAL CHARACTERISTICS OF THE SHORELINE AND OTHER FEATURES. TEMPORAL CHANGES MAY HAVE OCCURRED SINCE THIS DATA SET WAS COLLECTED AND SOME PARTS OF THE DATA MAY NO LONGER BE AN ACCURATE REPRESENTATION OF THE SURFACE CONDITIONS.

Scale in Feet
200 0 200 400 600

- Shoalest Sounding
- CenterLine
- ToeLine
- QuarterLine
- StationLine
- 35 - 48.39
- 34 - 35
- 33 - 34
- 32 - 33
- 31 - 32
- 30 - 31
- 19.69 - 30



VICINITY MAP

1. THIS SURVEY MEETS STANDARDS AS OUTLINED IN CORPS OF ENGINEERS' HYDROGRAPHIC SURVEY MANUAL EM1110-2-1003, DATED NOVEMBER 30, 2013 FOR NAVIGATION AND DREDGING SUPPORT SURVEYS.

2. HORIZONTAL REFERENCE - NAD 83, DELAWARE STATE PLANE, ZONE 0700, U.S. FOOT.

3. VERTICAL REFERENCE – MEAN LOWER LOW WATER, WHICH IS BELOW N.A.V.D. 88 BY THE FOLLOWING:
2. 62' from STA. 26+000 to STA. 25+516.80
2.64' from STA. 25+516.80 to STA. 24+586.34
2.66' from STA. 24+586.34 to STA. 23+655.72
2.68' from STA. 23+655.72 to STA. 22+448.76
2.70' from STA. 22+448.76 to STA. 21+672.19
2.72' from STA. 21+672.19 to STA. 20+895.63
2.73' from STA. 20+895.63 to STA. 20+119.06
2.75' from STA. 20+119.06 to STA. 19+342.49
2.95' from STA. 19+342.49 to STA. -0+400

4. GEOID 12B AND NOAA TIDAL EPOCH: 1983 – 2001 WERE USED. SOUNDINGS ARE EXPRESSED IN FEET AND TENTHS AND REFER TO MEAN LOWER LOW WATER.

5. SOUNDINGS WERE SELECTED FOR PLOTTING PURPOSES ONLY. USING THE MINIMUM DEPTH WITHIN A 30'X30' CELL SHIFTED TO THE CELL CENTER.

6. CONTOURS DEPICT ACTUAL LOCATION OF BATHYMETRY AND DO NOT NECESSARILY REFLECT PLOTTED SOUNDING LOCATIONS.

7. CONTOURS WERE GENERATED USING THE MINIMUM DEPTH WITHIN A 15'X15' CELL.

8. HYPACK, INC. SOFTWARE WAS USED TO PERFORM THE SOUNDING SELECTION AND CONTOUR GENERATION.

9. THE INFORMATION DEPICTED ON THIS MAP REPRESENT THE RESULTS OF SURVEYS MADE ON THE DATES INDICATED AND CAN ONLY BE CONSIDERED AS INDICATING THE GENERAL CONDITIONS EXISTING AT THAT TIME.

10. THE POSITIONS OF THE AIDS TO NAVIGATION ARE PROVIDED FOR INFORMATION ONLY, AND SHOULD NOT BE USED FOR NAVIGATION.

11. THE LIMITS OF THE FEDERAL CHANNEL DEPICT THE MOST CURRENT CHANNEL FRAMEWORK AVAILABLE WHICH CAN ALSO BE DOWNLOADED HERE:

http://navigation.usace.army.mil/Survey/Framework

12. BASE MAPPING LINEWORK OR ORTHOPHOTOGRAPHY HAS BEEN COMPILED FROM A VARIETY OF SOURCES AND DATES AND IS INTENDED TO PORTRAY GENERAL CHARACTERISTICS OF THE SHORELINE AND OTHER FEATURES. TEMPORAL CHANGES MAY HAVE OCCURRED SINCE THIS DATA SET WAS COLLECTED AND SOME PARTS OF THE DATA MAY NO LONGER BE AN ACCURATE REPRESENTATION OF THE SURFACE CONDITIONS.

Scale in Feet
200 0 200 400 600

- Shoalest Sounding
- CenterLine
- ToeLine
- QuarterLine
- StationLine

35 - 48.39
34 - 35
33 - 34
32 - 33
31 - 32
30 - 31
19.69 - 30

US Army Corps of Engineers
Philadelphia District

STA. 0+000 to STA. 14+000 -- 17 & 18 JAN 24
STA. 14+000 to STA. 24+000 -- 02 JAN 24
STA. 24+000 to STA. 29+700 -- 28 DEC 23

U.S. ARMY CORPS OF ENGINEERS
PHILADELPHIA DISTRICT

Surveyed By:
Plotted By: E. Anthony
Checked By:
Drawing No:
Plot Scale:
Approved: Chief, Survey Section

Chesapeake and Delaware Canal
Delaware River to St. Georges Bridges
Examination
STA. -0+400 TO STA. 26+000

E-CD-113



US Army Corps of Engineers
Philadelphia District

STA. 0+000 to STA. 14+000 -- 17 & 18 JAN 24
STA. 14+000 to STA. 24+000 -- 02 JAN 24
STA. 24+000 to STA. 29+700 -- 28 DEC 23

DISCLAIMER
The materials are provided for general information only and should not be used for navigation. The government makes no warranty as to the accuracy, completeness, or suitability for any particular purpose of the information provided. It is not intended for use as a navigation aid. NOAA charts and publications should be used for navigation. GIS files are provided "as is." The government disclaims all warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. The government does not guarantee that the files are free from errors, omissions, or inaccuracies. The government disclaims any responsibility for any errors or omissions in the files and for any consequences resulting from their use. The government makes no representations as to the truth, accuracy, or reliability of any statements or information contained in the files. The government disclaims any liability for the use of this data by others and the government shall not be liable for any damages, losses, or expenses arising from such use. The government reserves the right to modify or withdraw the files at any time without notice.

Surveyed By:
Plotted By: E. Anthony
Checked By:
Approved: Chief, Survey Section
Drawing No:
Plot Scale:
U.S. ARMY CORPS OF ENGINEERS
PHILADELPHIA DISTRICT

Chesapeake and Delaware Canal
Delaware River to St. Georges Bridges
Examination
STA. -0+400 TO STA. 26+000

E-CD-113



1. THIS SURVEY MEETS STANDARDS AS OUTLINED IN CORPS OF ENGINEERS' HYDROGRAPHIC SURVEY MANUAL EM1110-2-1003, DATED NOVEMBER 30, 2013 FOR NAVIGATION AND DREDGING SUPPORT SURVEYS.

2. HORIZONTAL REFERENCE - NAD 83, DELAWARE STATE PLANE, ZONE 0700, U.S. FOOT.

3. VERTICAL REFERENCE – MEAN LOWER LOW WATER, WHICH IS BELOW N.A.V.D. 88 BY THE FOLLOWING:
2. 62' from STA. 26+000 to STA. 25+516.80
2.64' from STA. 25+516.80 to STA. 24+586.34
2.66' from STA. 24+586.34 to STA. 23+655.72
2.68' from STA. 23+655.72 to STA. 22+448.76
2.70' from STA. 22+448.76 to STA. 21+672.19
2.72' from STA. 21+672.19 to STA. 20+895.63
2.73' from STA. 20+895.63 to STA. 20+119.06
2.75' from STA. 20+119.06 to STA. 19+342.49
2.95' from STA. 19+342.49 to STA. -0+400

4. GEOID 12B AND NOAA TIDAL EPOCH: 1983 – 2001 WERE USED. SOUNDINGS ARE EXPRESSED IN FEET AND TENTHS AND REFER TO MEAN LOWER LOW WATER.

5. SOUNDINGS WERE SELECTED FOR PLOTTING PURPOSES ONLY, USING THE MINIMUM DEPTH WITHIN A 30'X30' CELL SHIFTED TO THE CELL CENTER.

6. CONTOURS DEPICT ACTUAL LOCATION OF BATHYMETRY AND DO NOT NECESSARILY REFLECT PLOTTED SOUNDING LOCATIONS.

7. CONTOURS WERE GENERATED USING THE MINIMUM DEPTH WITHIN A 15'X15' CELL.

8. HYPACK, INC. SOFTWARE WAS USED TO PERFORM THE SOUNDING SELECTION AND CONTOUR GENERATION.

9. THE INFORMATION DEPICTED ON THIS MAP REPRESENT THE RESULTS OF SURVEYS MADE ON THE DATES INDICATED AND CAN ONLY BE CONSIDERED AS INDICATING THE GENERAL CONDITIONS EXISTING AT THAT TIME.

10. THE POSITIONS OF THE AIDS TO NAVIGATION ARE PROVIDED FOR INFORMATION ONLY, AND SHOULD NOT BE USED FOR NAVIGATION.

11. THE LIMITS OF THE FEDERAL CHANNEL DEPICT THE MOST CURRENT CHANNEL FRAMEWORK AVAILABLE WHICH CAN ALSO BE DOWNLOADED HERE:

http://navigation.usace.army.mil/Survey/Framework

12. BASE MAPPING LINEWORK OR ORTHOPHOTOGRAPHY HAS BEEN COMPILED FROM A VARIETY OF SOURCES AND DATES AND IS INTENDED TO PORTRAY GENERAL CHARACTERISTICS OF THE SHORELINE AND OTHER FEATURES. TEMPORAL CHANGES MAY HAVE OCCURRED SINCE THIS DATA SET WAS COLLECTED AND SOME PARTS OF THE DATA MAY NO LONGER BE AN ACCURATE REPRESENTATION OF THE SURFACE CONDITIONS.

Scale in Feet
200 0 200 400 600

- Shoalest Sounding
- CenterLine
- ToeLine
- QuarterLine
- StationLine
- 35 - 48.39
- 34 - 35
- 33 - 34
- 32 - 33
- 31 - 32
- 30 - 31
- 19.69 - 30